

Lautsprecher PA > 18Sound > 21 Zoll > (StÄ¼ck) 18-sound 53cm Bass 21 NLW 9001

(StÄ¼ck) 18-sound 53cm Bass 21 NLW 9001



18
EIGHTEEN
SOUND
EighteenSound.com

Artikelnummer: 18S-21NLW9001

(StÄ¼ck) 18-sound 53cm Bass 21 NLW 9001

Hersteller: X!Max Lautsprechertechnik

21" ISV (Innen/außen gewickelte Spule), DSS (Doppelzentrierung), Demodulationsring zur Verringerung von Verzerrungen. 1800 W AES, 135mm VC, 96 dB/W/m, 8 Ohm, Xmax +/-14mm. Beschichtete Membran. Neodymmagnetsystem, dadurch nur 14kg Gewicht. BR 150-350l

Key Features

- 98 dB SPL 1W / 1m average sensitivity
- 135 mm (5.3 in) split winding four layers ISV copper coil
- 3600 W program power handling
- Carbon fiber reinforced cellulose cone
- Double Silicon Spider (DSS) for improved excursion control
- Aluminum demodulating ring (SDR) for lower distortion
- Low noise forced ventilation design for low power compression
- Weather protected cone and plates for outdoor usage
- Suitable for vented and bandpass subwoofer systems

General Specifications

Nominal Diameter

533 mm (21 in)

Rated Impedance

8 Ohm

Lautsprecher PA > 18Sound > 21 Zoll > (StÄ¼ck) 18-sound 53cm Bass 21 NLW 9001

(StÄ¼ck) 18-sound 53cm Bass 21 NLW 9001

AES Power

1800W

Program Power

3600W

Peak Power

10000W

Sensitivity

98 dB

Frequency Range

25 - 1500 Hz

Power Compression @-10dB

0,7 dB

Power Compression @-3dB

1,5 dB

Power Compression @Full Power

2,2 dB

Max Recomm. Frequency

150 Hz

Lautsprecher PA > 18Sound > 21 Zoll > (StÄ¼ck) 18-sound 53cm Bass 21 NLW 9001

(StÄ¼ck) 18-sound 53cm Bass 21 NLW 9001

Recomm. Enclosure Volume

120 ÷ 500 lt (4,24 ÷ 17,7 cuft)

Minimum Impedance

7,6 Ohm at 25°C

Max Peak To Peak Excursion

70 mm (2,75 in)

Voice Coil Diameter

135 mm (5,3 in)

Voice Coil Technology

split winding, 4 layers copper wire

Suspension

Triple roll, Polycotton

Cone

Straight ribbed carbon fiber loaded cellulose

Thiele Small Parameters

Fs

32 Hz

Re

Lautsprecher PA > 18Sound > 21 Zoll > (StÄ¼ck) 18-sound 53cm Bass 21 NLW 9001

(StÄ¼ck) 18-sound 53cm Bass 21 NLW 9001

5,9 Ohm

Sd

0,1662 sq.mt. (257,6 sq.in.)

Qms

4,5

Qes

0,34

Qts

0,31

Vas

244 lt. (8,62 cuft)

Mms

390 gr. (0,86 lb)

BL

37 Tm

Linear Mathematical Xmax

±14 mm (±0,55 in)

Le (1kHz)

Lautsprecher PA > 18Sound > 21 Zoll > (StÃ¼ck) 18-sound 53cm Bass 21 NLW 9001

(StÃ¼ck) 18-sound 53cm Bass 21 NLW 9001

3,1 mH

Ref. Efficiency 1W@1m (half space)

95,5 dB

Mounting information

Overall diameter

545 mm (21,46 in)

N. of mounting holes and bolt

8

Mounting holes diameter

8,5 mm (0,33 in)

Bolt circle diameter

520 mm (20,47 in)

Front mount baffle cutout & slash;

492 mm (19,37 in)

Rear mount baffle cutout & slash;

490 mm (19,29 in)

Total depth

250 mm (9,8 in)

Lautsprecher PA > 18Sound > 21 Zoll > (StÃ¼ck) 18-sound 53cm Bass 21 NLW 9001

(StÃ¼ck) 18-sound 53cm Bass 21 NLW 9001

Flange and gasket thickness

18 mm (0,7 in)

Net weight

14 kg (30,9 lb)

Shipping weight

15,5 kg (34,2 lb)

CardBoard Packaging dimensions

570x570x290 mm (22,4x22,4x11,4 in)

Preis: 880,00 EUR [inkl. 19% MwSt zzgl. Versandkosten]

Im Shop aufgenommen am