

Lautsprecher PA > RCF > 18 Zoll > (Stück) RCF 46cm Tieftöner LF18N405

(Stück) RCF 46cm Tieftöner LF18N405

Artikelnummer: RCF-LF18N405

(Stück) RCF 46cm Tieftöner LF18N405

Hersteller: RCF



Incredibly linear frequency response characteristics, the highest power handling of any comparable 18-inch neodymium transducer, the lowest power compression.

The LF18N405 is an extended low frequency with high power handling, designed to provide powerful and accurate bass frequencies with low distortion, low power compression and very high SPL. The LF18N405 uses a fibre loaded cone assembly along a large triple roll surround, this combination provides remarkable strength and control. The single spider system is specifically designed with a heavy cloth which ensures excellent control during large excursions. A fully optimised T-pole design generates the minimum amount of flux modulation. The Dual-forced air venting magnetic structure system provides a very efficient voice coil ventilation to minimize the power compression.

Features

- 4 - inch, fiberglass inside-outside copper voice coil
- 300 Watt continuous program power handling
- 97 dB Sensitivity
- 30 Hz - 1 kHz Frequency range
- Hyperventated magnetic structure for minimum power compression
- Triple roll surround and exponential cone geometry

General Specifications

- Nominal Diameter: 460 / 18 mm/inch
- Rated Impedance: 8 Ω
- Program Power: 3000 W AES

Lautsprecher PA > RCF > 18 Zoll > (Stück) RCF 46cm Tieftöner LF18N405

(Stück) RCF 46cm Tieftöner LF18N405

- Power handling capacity: 1500 W AES
- Sensitivity: 97 dB
- Frequency Range: 30 Hz - 1000 Hz
- Effective Piston Diameter: 395 / 15.6 mm/inch
- Max Excursion Before Damage (peak to peak): 58 / 2.28 mm/inch
- Minimum Impedance: 6.0 Ω ;
- Voice Coil Diameter: 100 / 4 mm/inch
- Voice Coil Material: Copper
- Voice Coil Winding Depth: 36 / 1.41 mm/inch
- Number of layers: 2
- Kind of layer: inside / outside
- Top Plate Thickness: 15 / 0.6 mm/inch
- Cone Material: No pressed pulp
- Cone Design: Curved
- Surround Material: Polycotton
- Surround Design: Triple roll

Thiele/Small Parameters

- DC resistance: 4.9 Ω ;
- Mechanical factor: 7
- Electrical factor: 0.34
- Total factor: 0.32
- BL Factor: 25.4 T \cdot m
- Effective Moving Mass: 261 g
-

Lautsprecher PA > RCF > 18 Zoll > (Stück) RCF 46cm Tieftöner LF18N405

(Stück) RCF 46cm Tieftöner LF18N405

Equivalent Cas air load: 227 liters

- Effettive piston area: 0.122 m²;
- Max. linear excursion (mathematical): 14.2 mm
- Voice - coil inductance @ 1kHz: 1.7 mH
- Half-space efficiency: 1.70%

Mounting information

- Overall Diameter: 465 / 18.3 mm/inch
- Bolt Circle Diameter: 442-447 / 17.4-17.6 mm/inch
- Bolt Hole Diameter: 6.5 / 0.3 mm/inch
- Front Mount Baffle Cut-out: 424 / 16.7 mm/inch
- Rear Mount Baffle Cut-out: 424 / 16.7 mm/inch
- Depth: 190 / 7.48 mm/inch
- Volume occupied by the driver: 5.5 / 0.19 liters/ft³;
- Net Weight: 8.8 / 20.2 kg/lbs

Shipping information

- Shipping weight: 10 / 22 kg/lbs

Preis: 350,00 EUR [inkl. 19% MwSt zzgl. Versandkosten]

Lautsprecher PA > RCF > 18 Zoll > (Stück) RCF 46cm Tieftöner LF18N405

(Stück) RCF 46cm Tieftöner LF18N405

Im Shop aufgenommen am Sonntag, 11. Januar 2019

Achenbach Akustik